



Lube *notes*:

Design Engineers' Guide to Selecting a Lubricant

Lubricants for Potentiometers and Sliding Position Sensors

Potentiometers and other sliding position sensors are electromechanical devices whose performance and operating life can be dramatically improved through lubrication. Each of these devices has a metal wiper that moves along a resistive element, to regulate current flow to a device or to indicate when precalibrated positions are reached. The tracks may be any of a variety of conductive materials: wound metal wire, conductive plastic or ceramic compositions. Lubricating these tracks helps prevent wear, attenuate electrical noise and extend operating life.

Selecting Lubricants for Potentiometers and Other Electromechanical Sensors

Oil or grease. Wear prevention is the primary reason for potentiometer track lubrication. Most importantly, the lubricant film must be strong enough to prevent wear but thin enough throughout the operating range to prevent contact hydroplaning and resulting intermittancies. When working with small, delicate mechanisms with extremely low starting torque, oils may be required. However, greases, with their important stay-in-place advantage, have been the most successful potentiometer lubricants. Light, low shear greases, some approaching a semi-fluid state, can often be designed for even very low power applications.

Broad temperature film strength. Since it is the film of lubricant that prevents wear, good film strength is essential. While arcing is not usually a problem, high heat generated by resistance — the temperature can reach 225°C in automotive dimmer switches, for example — requires a lubricant to retain film strength over a broad temperature range.

Ambient conditions also affect lubricant selection. Very low temperatures cause some lubricants to become so viscous that they prevent motion. On the other hand, in underhood applications where performance-related devices are multiplying, extreme wide temperature and fuel-resistant lubricants have become a necessity.

A note about damping greases. Although not intended as track lubricants, Nye's Damping Greases are widely used on potentiometers and other rotary devices where shaft/bearing lubrication is needed to damp free motion and produce a "velvet feel." See our application summary on Damping Greases for details.

Selecting the right lubricant for your application. Following is a partial list of popular Nye lubricants used on tracks of potentiometers and other sliding position sensors. Additional oils and greases are available to meet a wide range of application requirements. For technical specifications, evaluation samples, or questions about any Nye products — or to discuss a lubricant *custom-designed* for your application — call us at (508) 996-6721. Nye is ready to work with you to ensure you make the best possible lubricant choice.

For the best choice in lubricants, Call Nye 508-996-6721

Lubricants for Potentiometers and Other Electromechanical Sensors	Temp Range (C°)	Applications
NyoSil M-25	-70 to 200	Complex silicone oil for long term wear protection, and traditional solution for wide-temp wirewound designs.
Fluorocarbon Gel 813-1	-70 to 200	Wide temperature complex silicone oil in chemically inert thickener. Excellent low-temp starting torque and noise reduction properties. Ideal choice for conductive plastic potentiometers.
NyoGel® 781A	-70 to 200	Very soft, complex silicone soap-gelled grease often used as an alternative to the fluorocarbon-gelled 813 series. Recommended where noise electrical noise reduction is a special concern.
Rheolube 716A	-54 to 150	Complex ester-based grease fortified with special additives to reduce electrical noise and wear in electrical contact applications. Good wide-temp serviceability. Base fluid has excellent film strength for very high-load applications. Use with caution around ester-vulnerable plastics.
UniFlor™ 8981	-65 to 250	Chemically resistant fluorinated grease with wide-temp fluidity, very low volatility, and exceptional high-temp stability. Lowest shear resistance for delicate low-temp applications.

Nye Lubricants, Inc.
12 Howland Rd.
Fairhaven, MA 02719
Phone: 508-996-6721
Fax: 508-997-5285

Because we cannot anticipate or control the many different conditions under which this information and our products may be used, we cannot guarantee the applicability of this information or the suitability of our products in any individual situation. For the same reason, the products discussed are sold without warranty, express or implied. Statements concerning the possible use of our products are not intended as recommendations to use our product in the infringement of any patent.