



Dulub Co. Ltd. www.dulub.com.tw tel : 886-7-536 5500 fax : 886-7-536 9977

Nye Automotive lubricants



1. **Actuator Lubricants** 汽車促動器潤滑油



2. **Cable Lubricants** 汽車拉索潤滑油



3. **Connector Lubricants** 汽車連接器潤滑油



4. **Electric Motor Lubricants** 汽車電動馬達潤滑油



5. **Powertrain Lubricants** 汽車動力鏈潤滑油



6. **Sensor Lubricants** 汽車傳感器潤滑油



7. **Steering and Suspension Lubricants** 汽車轉向及懸吊底盤潤滑油



8. **Switch Lubricants** 汽車開關潤滑油

1. Actuator Lubricants 汽車促動器潤滑油



Nye actuator lubricants not only get you through rigorous, rapid-cycle testing, they maximize the operating life of your design. Choose from metal, plastic, and rubber-compatible lubricants, each engineered specifically for the slides, cams, gears, and other mechanisms found in automotive actuators. Nye offers actuator greases that are impervious to water, salt water, underhood fluids, and wide temperature fluctuations. For hand-operated actuators, our greases quiet mechanical noise and allow you to select the tactile "feel" most appropriate for the device.

1. **ABS** 防鎖死煞車系統
2. *Airbag Clock Spring* 安全氣囊
3. *Climate Control* 空調控制
4. *Cup Holders* 置杯架
5. *Door Lock* 門鎖
6. *Exterior Mirror* 車外後視鏡
7. *Grab Handles* 車內把手
8. *Hinges* 絞鏈
9. *Key Cylinders* 鑰匙圓筒
10. *Latches* 門闕
11. *Pedals* 踏板
12. *Power Sliding Door* 電動滑門
13. *PRNDL* 自排桿總成
14. *Seat Position* 座椅位置控制
15. *Vent Controls* 通風孔控制
16. *Visors* 遮陽板
17. *Window Lift* 窗戶升降

1. ABS 防鎖死煞車系統

[UniFlor 8512R.pdf](#)

(-50 to 225C) economical, brake fluid resistant grease, rust inhibited

[UniFlor 8512S.pdf](#)

(-50 to 225C) EPDM compatible, brake fluid resistant, solenoid grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

[UniFlor 8981X.pdf](#)

(-60 to 200C) very low temp, brake fluid resistant bearing grease

2. AIRBAG CLOCK SPRING 安全氣囊

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 885ST.pdf](#)

(-50 to 200C) eliminates clockspring noise and wear

[UniFlor 8921.pdf](#)

(-60 to 250C) very wide temp., very efficient grease

[UniFlor 8951.pdf](#)

(-90 to 250C) very low temp. and capable clock spring grease

3. CLIMATE CONTROL 空調控制

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 779.pdf](#)

(-40 to 125C) for smooth feel and control

4. CUP HOLDERS 置杯架

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 779.pdf](#)

(-40 to 125C) for smooth feel and control

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

5. DOOR LOCK 門鎖

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

6. EXTERIOR MIRROR 車外後視鏡

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

7. GRAB HANDLES 車內把手

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

8. HINGES 絞鏈

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

9. KEY CYLINDERS 鑰匙圓筒

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

10.LATCHES 門門

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

11.PEDALS 踏板

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 363F.pdf](#)

(-40 to 125C) wide temp, low friction bearing and gear grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

12.POWER SLIDING DOOR 電動滑門

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 759T.pdf](#)

(-40 to 125C) salt water resistant, very efficient track grease

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

13. PRNDL 自排桿總成

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

14. SEAT POSITION 座椅位置控制

[Rheolube 380.pdf](#)

(-40 to 125C) high load gear and bearing grease

[Nyogel 759T.pdf](#)

(-40 to 125C) non-staining, very efficient track grease

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

15. VENT CONTROLS 通風孔控制

[Nyogel 774VH.pdf](#)

(-40 to 125C) plastic compatible, heavy damped feel

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

16. ISORS 遮陽板

[Rheolube 363F.pdf](#)

(-40 to 125C) proven visor hinge grease

[Nyogel 774VH.pdf](#)

(-40 to 125C) plastic compatible, heavy damped feel

[Nyogel 779.pdf](#)

(-40 to 125C) for smooth feel and control

17.WINDOW LIFT 窗戶升降

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 723GR.pdf](#)

(-40 to 125C) wide temp., noise reducing, water resistant

[Nyogel 744F-MS.pdf](#)

(-40 to 125C) proven to eliminate squeaking, long life grease

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

2. Cable Lubricants 汽車拉索潤滑油



Nye's cable lubricants deliver the smooth, quick, responsive operation you want from cable assemblies — from -40°C to 150°C . Engineered to wet and adhere to the cable and liner surfaces, these lubricants are super efficient, pushing cable assemblies well beyond the requirements of today's demanding cycling tests. They also improve the perceived quality of hand-operated cables by mechanically reducing vibration, thereby eliminating undesirable noise and annoying tactile sensations.

1. **Brake** 煞車
2. **Climate Control** 空調控制
3. **Clutch** 離合器
4. **Exterior Mirror** 車外後視鏡
5. **Fuel Door Release** 油箱門
6. **Hood Release** 引擎蓋
7. **Parking Brake** 手煞車
8. **Seat Recline** 座椅靠背
9. **Speedometer** 速度表
10. **Sunroof** 天窗
11. **Throttle** 節流閥
12. **Transmission** 傳動件
13. **Trunk Release** 後行李箱釋放
14. **Window Regulator** 車窗升降機

1. BRAKE 煞車

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Flourocarbon Gel 880MS.pdf](#)

(-40 to 200C) high load version of 880

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited, plastic compatible

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

2. CLIMATE CONTROL 空調控制

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 779.pdf](#)

(-40 to 125C) for smooth feel and control

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

3. CLUTCH 離合器

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

4. EXTERIOR MIRROR 車外後視鏡

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

5. FUEL DOOR RELEASE 油箱門

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Instrument Grease 732C.pdf](#)

(-50 to 150C) wide temp., salt water resistant

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, gasoline resistant, rust inhibited

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

6. HOOD RELEASE 引擎蓋

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

7. PARKING BRAKE 手煞車

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Flourocarbon Gel 880MS.pdf](#)

(-40 to 200C) high load version of 880

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

8. SEAT RECLINE 座椅靠背

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

9. SPEEDOMETER 速度表

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Flourocarbon Gel 880MS.pdf](#)

(-40 to 200C) high load version of 880

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

10. SUNROOF 天窗

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Nyogel 729F.pdf](#)

(-50 to 125C) wide temp., soft and salt water resistant

[Rheolube 739A.pdf](#)

(-50 to 125C) excellent low temp performance

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

11. THROTTLE 節流閥

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Rheolube 739A.pdf](#)

(-50 to 125C) excellent low temp performance

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, gasoline resistant, rust inhibited

12. TRANSMISSION 傳動件

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

13. TRUNK RELEASE 後行李箱釋放

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) for long cables, rust inhibited

14. WINDOW REGULATOR 車窗升降機

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheosil 500F.pdf](#)

(-50 to 200C) maintains good efficiency over long life

[Rheolube 723GR.pdf](#)

(-40 to 125C) wide temp., noise reducing, water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

3.Connector Lubricants 汽車連接器潤滑油



Nye connector lubricants minimize common electrical problems, a major warranty cost for automakers. For traditional tin/lead and noble metal connectors, they reduce fretting and environmental corrosion, common causes of erratic operation and premature failure. They also cut insertion forces by as much as 80 percent. For fiber optic data, illumination, and display applications, Nye's SmartGels™ serve as a "index-matching" bridge to ensure maximum signal transmission. Whatever role connectors play in your design, Nye has the lubricant you need.

1. **ABS** 防鎖死煞車系統
2. *Airbag* 安全氣囊
3. *Alternator* 發電機
4. *Battery* 電瓶
5. *Cooling Fan* 散熱風扇
6. *ECM-ECU* (Electronic Control Module-Electronic Control Unit)電子控制模組
7. *EGR* (Exhaust Gas Recirculation)廢氣再循環系統
8. *Firewall* 防火牆
9. *Fuel Sender* 送油器
10. *Headlamp-Tail Lamp* 頭尾燈
11. *Mass Air Flow* 大量空氣流動裝置
12. *Multifunction Switch* 多功能開關
13. *O2* 氧氣
14. *Speakers* 音響喇叭
15. *Starter* 起動機
16. *TPS* (Throttle Position Sensor) 節流閥位置傳感器
17. *TRS* (Transmission Range Sensor)傳動幅度傳感器
18. *WheelSpeedSensor* 輪速傳感器

1.ABS 防鎖死煞車系統

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive, salt water resistant, anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nysil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

2. AIRBAG 安全氣囊

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive, salt water resistant, anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

3. ALTERNATOR 發電機

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive, salt water resistant, anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

4. BATTERY 電瓶

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive, salt water resistant, anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

5. COOLING FAN 散熱風扇

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

6. ECM-ECU 電子控制模組

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

7. EGR (*Exhaust Gas Recirculation*) 廢氣再循環系統

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

8. FIREWALL 防火牆

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

9. FUEL SENDER 送油器

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

10. HEADLAMP/TAIL LAMP 頭尾燈

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

11. MASS AIR FLOW 大量空氣流動裝置

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

12. MULTIFUNCTION SWITCH 多功能開關

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

13. O2 氧氣

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

14. SPEAKERS 音響喇叭

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

15. STARTER 起動機

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

[UniFlor 8512.pdf](#)

(-50 to 225C) superior insertion reducing lubricant

[Nyosil M25.pdf](#)

(-60 to 200C) stamping, anti-fretting fluid

16. TPS 節流閥位置傳感器

[Nyogel 760G.pdf](#)

(-40 to 125C) proven automotive anti-fretting lubricant

[Fluorocarbon Gel 813-1.pdf](#)

(-60 to 200C) proven high temp., anti-fretting lubricant

UniFlor 8512.pdf

(-50 to 225C) superior insertion reducing lubricant

Nyosil M25.pdf

(-60 to 200C) stamping, anti-fretting fluid

17. TRS 傳動幅度傳感器

Nyogel 760G.pdf

(-40 to 125C) proven automotive anti-fretting lubricant

Fluorocarbon Gel 813-1.pdf

(-60 to 200C) proven high temp., anti-fretting lubricant

UniFlor 8512.pdf

(-50 to 225C) superior insertion reducing lubricant

Nyosil M25.pdf

(-60 to 200C) stamping, anti-fretting fluid

18. WHEEL SPEED SENSOR 輪速傳感器

Nyogel 760G.pdf

(-40 to 125C) proven automotive anti-fretting lubricant

Fluorocarbon Gel 813-1.pdf

(-60 to 200C) proven high temp., anti-fretting lubricant

UniFlor 8512.pdf

(-50 to 225C) superior insertion reducing lubricant

Nyosil M25.pdf

(-60 to 200C) stamping, anti-fretting fluid

4. Electric Motor Lubricants 汽車電動馬達潤滑油



With up to 60 motors in a typical automobile, Nye has engineered a broad family of electrical motor lubricants. All ensure low noise and maximum output efficiency from -40°C to 150°C . Tailored to the operating environment, Nye has lubricants that resist water, salt water, and underhood fluids; quiet the cold temperature hooting associated with some underhood motors; dissipate static electricity to reduce safety hazards in fuel pump motors; and eliminate the problem of low-temperature

torque — even for flea-powered motors

1. *ABS* 防鎖死煞車系統
2. *Antenna* 天線
3. *Cooling Fan* 散熱風扇
4. *Electric Brake* 電動煞車
5. *Electric Steering* 電動方向盤
6. *ETC* 電子控制節氣閥門
7. *Fuel Pump* 汽油幫浦
8. *HVAC Blower (Heater-Vent-Air Conditioning)* 暖氣出風口調節
9. *Power Mirror* 電動後視鏡
10. *Seat* 座椅
11. *Sunroof* 天窗
12. *Starter* 起動器
13. *Trunk Pulldown* 後行李箱摺疊
14. *Window* 車窗
15. *Wiper* 雨刷

1. ABS 防鎖死煞車系統

[Rheolube 375.pdf](#)

(-40 to 125C) wide temp bearing grease, rust inhibited

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[UniFlor 8512R.pdf](#)

(-50 to 225C) economical, brake fluid resistant grease, rust inhibited

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

2. ANTENNA 天線

[Rheolube 363F.pdf](#)

(-40 to 125C) wide temp, low friction bearing and gear grease

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[Rheolube 723GR.pdf](#)

(-40 to 125C) wide temp., noise reducing, water resistant

[UniFlor 8511.pdf](#)

(-50 to 225C) very wide temp., plastic compatible gear and bearing grease

3.COOLING FAN 散熱風扇

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8920.pdf](#)

(-60 to 250C) very wide temp, non varnishing sintered bearing oil

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

4.ELECTRIC BRAKE 電動煞車

[Rheolube 375.pdf](#)

(-40 to 125C) wide temp bearing grease, rust inhibited

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[UniFlor 8512R.pdf](#)

(-50 to 225C) economical, brake fluid resistant grease, rust inhibited

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

5.ELECTRIC STEERING 電動方向盤

[Rheolube 380C.pdf](#)

(-40 to 125C) high load gear and bearing grease

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[Nyogel 774VL.pdf](#)

(-50 to 125C) efficient, noise reducing gear and bearing grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

6.ETC 電子控制節氣閥門

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8512R.pdf](#)

(-50 to 225C) economical, brake fluid resistant grease, rust inhibited

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

[UniFlor 8981X.pdf](#)

(-60 to 200C) very low temp, brake fluid resistant bearing grease

7.FUEL PUMP 汽油幫浦

[UniFlor 8511E.pdf](#)

(-50 to 225C) high load, gasoline resistant bearing grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) economical, gasoline resistant grease, rust inhibited

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

[UniFlor 8981X.pdf](#)

(-60 to 200C) very low temp, brake fluid resistant bearing grease

8.HVAC BLOWER 暖氣出風口調節

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8920.pdf](#)

(-60 to 250C) very wide temp, non varnishing sintered bearing oil

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, brake fluid resistant, rust inhibited

9.POWER MIRROR 電動後視鏡

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Nyogel 774VL.pdf](#)

(-50 to 125C) efficient, noise reducing gear and bearing grease

[UniFlor 8511.pdf](#)

(-50 to 225C) very wide temp., plastic compatible gear and bearing grease

[Fluorocarbon Gel 880.pdf](#)

very smooth and efficient over a wide temp. range

10.SEAT 座椅

[Rheolube 363F.pdf](#)

(-40 to 125C) wide temp, low friction bearing and gear grease

[Rheolube 706CS.pdf](#)

(-50 to 150C) reduces motor brush noise on commutator

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[UniFlor 8511.pdf](#)

(-50 to 225C) very wide temp., plastic compatible gear and bearing grease

11.SUNROOF 天窗

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 706CS.pdf](#)

(-50 to 150C) reduces motor brush noise on commutator

[Nyogel 774VL.pdf](#)

(-50 to 125C) efficient, noise reducing gear and bearing grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited gear grease

12.STARTER 起動器

[Rheolube 377AL.pdf](#)

(-40 to 125C) proven extreme pressure gear grease

[Rheolube 380.pdf](#)

(-40 to 135C) proven wide temp, extreme pressure gear grease

[Nyogel 774H.pdf](#)

(-40 to 125C) non staining, non dripping, light damping grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited gear grease

13.TRUNK PULLDOWN 後行李箱摺疊

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 363F.pdf](#)

(-40 to 125C) wide temp, low friction bearing and gear grease

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

14.WINDOW 車窗

[Rheolube 362HB.pdf](#)

(-40 to 125C) wide temp, efficient and water resistant

[Rheolube 363F.pdf](#)

(-40 to 125C) wide temp, low friction bearing and gear grease

[Rheolube 723GR.pdf](#)

(-40 to 125C) wide temp., noise reducing, water resistant

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

15. WIPER 雨刷

[Rheolube 723GR.pdf](#)

(-40 to 125C) wide temp., noise reducing, water resistant

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[Rheolube 790G.pdf](#)

(-40 to 125C) high load, water resistant gear grease

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible

5. Powertrain Lubricants 汽車動力輪鏈潤滑油



A well-designed powertrain delivers more engine efficiency, better fuel economy, and a quieter drive. Nye's alternator, differential, U joint, wheel bearing, and other powertrain lubricants are designed to help you achieve these goals. Transferring power with minimal heat and noise, these lubricants are designed specifically for start/stop conditions, high and low speed operation, and heavy loads. Resistance to water, salt water, road grit, and harsh underhood fluids is standard.

1. *Condenser* 冷凝器
2. *CV Joint* 等速接頭
3. *Differential* 差速器
4. *Drum Brakes* 鼓式煞車
5. *Fuel System* 供油系統
6. *Idler Pulley* 惰輪
7. *Idle Air Actuator* 惰速空氣促動器
8. *Master Cylinder* 總泵
9. *Shifters* 排檔機構
10. *Slip Yokes* 滑軛
11. *Super Charger* 增壓器
12. *Throttle Plate* 節流板
13. *Transfer Case* 轉換箱
14. *U Joints:U* 型接頭
15. *Water Pump* 水幫浦
16. *Wheel Bearings* 車輪軸承

1. CONDENSER 冷凝器

[Rheotemp 500.pdf](#)

(-50 to 175C) high load, high speed bearing grease

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8751.pdf](#)

(-60 to 250C) very High temp, high load bearing grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very high temp, long life bearing grease

2. CV JOINT 等速接頭

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8751.pdf](#)

(-60 to 250C) very High temp, high load bearing grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very high temp, long life bearing grease

3.DIFFERENTIAL 差速器

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8751.pdf](#)

(-60 to 250C) very High temp, high load bearing grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very high temp, long life bearing grease

4.DRUM BRAKES 鼓式煞車

[Nyogel 774MS.pdf](#)

(-40 to 125C) excellent stay-in-place, water resistant grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) rust inhibited, very high temp, salt water resistant grease

[Fluorocarbon Gel 880.pdf](#)

high temp, stay-in-place, salt water resistant grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) rust inhibited, high temp, salt water resistant grease

5.FUEL SYSTEM 供油系統

[Nyogel 760G.pdf](#)

(-40 to 125C) salt water resistant connector grease

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) fuel resistant, low temp ink resistor grease

[UniFlor 8981.pdf](#)

(-65 to 250C) fuel resistant, light contact force ink resistor grease

6.IDLER PULLEY 惰輪

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8751.pdf](#)

(-60 to 250C) very High temp, high load bearing grease

[UniFlor 8921.pdf](#)

(-60 to 250C) fuel resistant, low temp ink resistor grease

7.IDLE AIR ACTUATOR 惰速空氣促動器

[Nyogel 741E.pdf](#)

(-60 to 200C) excellent low temp, stepper motor grease

[UniFlor 8512.pdf](#)

(-50 to 225C) wide temp, fuel resistant stepper motor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) very wide temp, fuel resistant bearing grease

[UniFlor 8971.pdf](#)

(-90 to 250C) excellent low temp, fuel resistant stepper grease

8.MASTER CYLINDER 總泵

[UniFlor 8512.pdf](#)

(-50 to 225C) wide temp, fuel resistant stepper motor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) brake fluid resistant, low temp, EPDM compatible grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) very efficient, rust inhibited, salt water resistant grease

9.SHIFTERS 排檔機構

[Rheolube 362HB.pdf](#)

(-40 to 125C) low slip stick, efficient grease

[Nyogel 774VL.pdf](#)

(-40 to 125C) velvet feel, noise reducing grease

[UniFlor 8512.pdf](#)

(-50 to 225C) high temp, rust inhibited, very low torque grease

[UniFlor 8921.pdf](#)

(-60 to 250C) Very wide temp, long life bearing grease

10.SLIP YOKES 滑軛

[Nyogel 774MS.pdf](#)

(-40 to 125C) excellent stay-in-place, water resistant grease

[UniFlor 8521.pdf](#)

(-40 to 250C) rust inhibited, very high temp, salt water resistant grease

[Fluorocarbon Gel 880.pdf](#)

high temp, stay-in-place, salt water resistant grease

Fluorocarbon Gel 990A-RP.pdf

(-40 to 200C) rust inhibited, high temp, salt water resistant grease

11.SUPER CHARGER 增壓器

Rheotemp 500.pdf

(-40 to 175C) proven high temp bearing grease

Synthetic Oil 605.pdf

(-40 to 150C) proven gear and sump oil

UniFlor 8512R.pdf

(-50 to 225C) high temp, rust inhibited, very low torque grease

UniFlor 8920.pdf

(-60 to 250C) very wide temp, gear and sump oil

12.THROTTLE PLATE 節流板

Rheolube 390A.pdf

(-40 to 125C) low oil separation bearing grease

Rheolube 789DM.pdf

(-40 to 150C) wide temp, salt water resistant

UniFlor 8512R.pdf

(-50 to 225C) high temp, rust inhibited, very low torque grease

UniFlor 8751.pdf

(-60 to 250C) very High temp, high load bearing grease

13.TRANSFER CASE 轉換箱

Synthetic Gear Oil 342.pdf

(-40 to 125C) wide temp gear oil

Synthetic Gear Oil 344.pdf

(-40 to 125C) wide temp, high load gear oil

Synthetic Gear Oil 345.pdf

(-40 to 125C) heavy duty, wide temp gear oil

Synthetic Oil 605.pdf

(-40 to 250C) high temp gear oil

14.U JOINTS U 型接頭

Rheolube 789DM.pdf

(-40 to 150C) wide temp, salt water resistant

Rheolube 797.pdf

(-30 to 180C) high temp., excellent roll stability bearing grease

UniFlor 8751.pdf

(-60 to 250C) very High temp, high load bearing grease

UniFlor 8921R.pdf

(-60 to 250C) very high temp, long life bearing grease

15. WATER PUMP 水幫浦

Rheolube 789DM.pdf

(-40 to 150C) wide temp, salt water resistant

Rheolube 797.pdf

(-30 to 180C) high temp., excellent roll stability bearing grease

UniFlor 8751.pdf

(-60 to 250C) very High temp, high load bearing grease

UniFlor 8921R.pdf

(-60 to 250C) very high temp, long life bearing grease

16. WHEEL BEARINGS 車輪軸承

Rheolube 797.pdf

(-30 to 180C) high temp., excellent roll stability bearing grease

UniFlor 8751.pdf

(-60 to 250C) very High temp, high load bearing grease

UniFlor 8921R.pdf

(-60 to 250C) very high temp, long life bearing grease

6.Sensor Lubricants 汽車傳感器潤滑油



The accuracy and operating life of automotive sensors are directly related to the quality of the lubricant used on both sensitive electrical and mechanical components. To meet a broad range of design needs, Nye offers light, low-shear sensor greases for very low power applications; sensor lubricants with exceptional film strength to accommodate heat generated by resistance; thermally conductive lubricants that boost the accuracy of temperature sensors; and unique underhood sensor lubricants that withstand years of vibration, thermal cycling, temperature extremes, as well as salt spray, sand, road grit, and underhood fluids.

1. *Exhaust Gas Recirculating* 廢氣再循環系統
2. *Fuel Level* 汽油箱油位
3. *Oil Pressure* 汽油油壓
4. *Pedal Position* 踏板位置
5. *Power Mirror Position* 電動後視鏡位置
6. *Seat Position* 座椅位置
7. *Temperature* 溫度
8. *Throttle Position* 節流閥位置
9. *Transmission Speed* 傳動器速度

1. EXHAUST GAS RECIRCULATING 廢氣再循環系統

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) fuel resistant, low temp ink resistor grease

[UniFlor 8951.pdf](#)

(-90 to 250C) eliminates low temp hydroplaning resistor grease

[UniFlor 8981.pdf](#)

(-65 to 250C) fuel resistant, light contact force ink resistor grease

2. FUEL LEVEL 汽油箱油位

[Nyetact 571H-10.pdf](#)

(-60 to 250C) fuel resistant, solvent dispersion

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) fuel resistant, low temp ink resistor grease

[UniFlor 8981.pdf](#)

(-65 to 250C) fuel resistant, light contact force ink resistor grease

3. OIL PRESSURE 汽油油壓

[Nyogel 741E.pdf](#)

(-60 to 200C) excellent low temp, potentiometer grease

[Fluorocarbon Gel 813S-1.pdf](#)

(-90 to 200C) proven low noise grease

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

[UniFlor 8981.pdf](#)

(-65 to 250C) fuel resistant, light contact force ink resistor grease

4. PEDAL POSITION 踏板位置

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Fluorocarbon Gel 813S-1.pdf](#)

(-90 to 200C) proven low noise grease

[UniFlor 8512.pdf](#)

(-50 to 225C) extremely efficient and plastic compatible grease

5. POWER MIRROR POSITION 電動後視鏡位置

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Fluorocarbon Gel 813S-1.pdf](#)

(-90 to 200C) proven low noise grease

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

6. SEAT POSITION 座椅位置

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Fluorocarbon Gel 813S-1.pdf](#)

(-90 to 200C) proven low noise grease

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

7. TEMPERATURE 溫度

[UniFlor 8955.pdf](#)

(-90 to 250C) very wide temperature, non varnishing compound

[Heat Sink Compound 920.pdf](#)

(-40 to 150C) proven non-silicone heat transfer material

[Heat Sink Compound 925.pdf](#)

(-50 to 200C) proven silicone heat transfer material

8. THROTTLE POSITION 節流閥位置

[UniFlor 8512.pdf](#)

(-50 to 225C) fuel resistant, all purpose ink resistor grease

[UniFlor 8921.pdf](#)

(-60 to 250C) fuel resistant, low temp ink resistor grease

[UniFlor 8950.pdf](#)

(-90 to 250C) eliminates low temp hydroplaning

[UniFlor 8981.pdf](#)

(-65 to 250C) fuel resistant, light contact force ink resistor grease

9. TRANSMISSION SPEED 傳動器速度

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Fluorocarbon Gel 813S-1.pdf](#)

(-90 to 200C) proven low noise grease

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

[UniFlor 8950.pdf](#)

(-90 to 250C) eliminates low temp hydroplaning

7. Steering and Suspension Lubricants 汽車轉向及懸吊底盤潤滑油



Vehicles used to have grease fittings simply because the original grease wasn't designed for the life of the component. All Nye's steering and suspension lubricants are. They eliminate squeaks and rattles from power steering gears, ball joints, shock absorbers, and other mechanisms. They also are engineered to resist water and salt water, tolerate high loads and vibration, and minimize friction and wear — even on rough terrain where steering and suspension components take a beating.

1. *Ball Joint* 球形接頭
2. *Idler Arm* 惰臂
3. *Intermediate Shaft* 中段轉軸
4. *Leaf Springs* 葉片式彈簧
5. *Manual Steering* 手動轉向
6. *Pitman Arm* 連接桿臂
7. *Power Steering Gear* 動力轉向齒輪
8. *Rack and Pinion Steering* 齒條小齒輪轉向
9. *Shaft Bearings* 轉軸軸承
10. *Shock Absorbers* 避震器
11. *Stabilizer Bushings* 穩定器軸襯
12. *Steering Yoke* 轉向軛
13. *Strut Bearing* 滑柱支撐軸承
14. *Tierods* 橫拉桿
15. *Tilt and Telescope* 偏向及方向盤轉軸

1. BALL JOINT 球形接頭

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

2. IDLER ARM 惰臂

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

3. INTERMEDIATE SHAFT 中段轉軸

[Rheotemp 500.pdf](#)

(-40 to 175C) proven high temp bearing grease

[Nyogel 774MS.pdf](#)

(-40 to 125C) excellent stay-in-place, water resistant grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

4. LEAF SPRINGS 葉片式彈簧

[Nyogel 767A.pdf](#)

(-30 to 125C) high load, water resistant, noise reducing grease

[Nyogel 774VH.pdf](#)

(-30 to 125C) proven extreme pressure, squeak eliminating grease

[UniFlor 8172.pdf](#)

(-30 to 225C) very wide temperature, squeak eliminating grease

[Fluorocarbon Gel 880.pdf](#)

very efficient, salt water resistant grease

5. MANUAL STEERING 手動轉向

[Synthetic Gear Oil 345.pdf](#)

(-40 to 125C) heavy duty, wide temp gear oil

[Rheolube 377AL.pdf](#)

(-40 to 125C) proven extreme pressure gear grease

[Rheolube 380.pdf](#)

(-40 to 135C) proven wide temp, extreme pressure gear grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

6. PITMAN ARM 連接桿臂

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

7. POWER STEERING GEAR 動力轉向齒輪

[Synthetic Gear Oil 345.pdf](#)

(-40 to 125C) heavy duty, wide temp gear oil

[Rheolube 377AL.pdf](#)

(-40 to 125C) proven extreme pressure gear grease

[Rheolube 380.pdf](#)

(-40 to 135C) proven wide temp, extreme pressure gear grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

8. RACK AND PINION STEERING 齒條小齒輪轉向

[Rheolube 380.pdf](#)

(-40 to 135C) proven wide temp, extreme pressure gear grease

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

9. SHAFT BEARINGS 轉軸軸承

[Rheolube 368AX-1](#)

(-40 to 125C) wide temp, high load bearing grease

[Rheolube 789DM.pdf](#)

(-40 to 150C) wide temp, salt water resistant

[Rheolube 797.pdf](#)

(-30 to 180C) high temp., excellent roll stability bearing grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

10. SHOCK ABSORBERS 避震器

[Synthetic Oil 176F.pdf](#)

(-50 to 125C) ideal for adjusting suspension

[Synthetic Oil 334.pdf](#)

(-40 to 100C) EPDM compatible assembly aid

[Synthetic Oil 605.pdf](#)

(-40 to 150C) high temperature, long life fluid

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

11. STABILIZER BUSHINGS 穩定器軸襯

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[Fluorocarbon Gel 990A-RP.pdf](#)

(-40 to 200C) very efficient, rust inhibited, salt water resistant grease

12. STEERING YOKE 轉向軛

[Rheolube 380.pdf](#)

(-40 to 135C) proven wide temp, extreme pressure gear grease

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

13. STRUT BEARING 滑柱支撐軸承

[Rheolube 390A.pdf](#)

(-40 to 125C) low oil separation bearing grease

[Nyogel 758G.pdf](#)

(-40 to 125C) salt water resistant sealing grease

[UniFlor 8512R.pdf](#)

(-50 to 225C) high temp, rust inhibited, low torque grease

[Fluorocarbon Gel 880.pdf](#)

very efficient, salt water resistant grease

14. Tierods 橫拉桿

[Fluorocarbon Gel 875MS.pdf](#)

(-40 to 125C) for heavily loaded, metal to metal interfaces

[Fluorocarbon Gel 875R.pdf](#)

(-40 to 125C) wide temp, eliminates slip stick

[Fluorocarbon Gel 880.pdf](#)

high temp, wear resistant, efficient grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

15. TILT AND TELESCOPE 偏向及方向盤轉軸

[Rheolube 380C.pdf](#)

(-40 to 125C) high load gear and bearing grease

[Rheolube 716R.pdf](#)

(-40 to 150C) wide temp, low noise bearing grease, rust inhibited

[Nyogel 774VL.pdf](#)

(-50 to 125C) efficient, noise reducing gear and bearing grease

[UniFlor 8921R.pdf](#)

(-60 to 250C) very wide temp, non-varnishing, rust inhibited

8.Switch Lubricants 汽車開關潤滑油



Designed to meet the 3X life standard, Nye switch lubricants are available for tin, copper, brass, and noble metal contacts. Tailored to low, medium, or high current switches and formulated for light, medium or heavy loads, these lubricants guard against milivolt drop, open circuit resistance problems, and "-40°C contact bounce." Underhood, they withstand thermal cycling and temperature extremes, from -90° to 250°C. They also resist humidity, dust, water, salt water, fuel, and underhood fluids. For the mechanical parts of a switch, Nye's family of "damping greases" provides an economical way to control the sound and feel of a switch.

1. *Airbag Cutoff* 安全氣囊切斷
2. *Climate Control* 空調控制
3. *Dash Panel Dimmer* 儀表板調光器
4. *Dual Stalk* 雙向柄
5. *Hazard* 警示
6. *Headlamp* 頭燈
7. *Ignition* 點火
8. *Multifunction* 多功能
9. *Power Lock* 電動鎖
10. *Power Mirror* 電動後視鏡
11. *Power Seat* 電動座椅
12. *Reading Lamp* 閱讀燈
13. *Rear Defrost* 後除霧
14. *TRS(Transmission Range Sensor)*傳動幅度感應
15. *Trunk Release* 後行李箱蓋鬆脫
16. *Turn Signal* 方向燈
17. *Window Lift* 電動窗升降

1.AIRBAG CUTOFF 安全氣囊切斷

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

2. CLIMATE CONTROL 空調控制

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 782G.pdf](#)

(-40 to 100C) clean burning, arcing contact grease

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

3. DASH PANEL DIMMER 儀表板調光器

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

4. DUAL STALK 雙向柄

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

5. HAZARD 警示

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 782G.pdf](#)

(-40 to 100C) clean burning, arcing contact grease

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

6. HEADLAMP 頭燈

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

7. IGNITION 點火

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 782G.pdf](#)

(-40 to 100C) clean burning, arcing contact grease

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

8. MULTIFUNCTION 多功能

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[Nyogel 782G.pdf](#)

(-40 to 100C) clean burning, arcing contact grease

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

9. POWER LOCK 電動鎖

[Rheolube 368.pdf](#)

(-40 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

10. POWER MIRROR 電動後視鏡

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8511.pdf](#)

(-50 to 225C) soft, efficient, non burning grease

11. POWER SEAT 電動座椅

[Rheolube 368.pdf](#)

(-40 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

12. READING LAMP 閱讀燈

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

13. REAR DEFROST 後除霧

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

14. TRS 傳動幅度感應

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

15. TRUNK RELEASE 後行李箱蓋鬆脫

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

16. TURN SIGNAL 方向燈

[Rheolube 362HT.pdf](#)

(-50 to 125C) wide temp., elec/mech. grease

[Rheolube 716A.pdf](#)

(-50 to 150C) light contact, elec/mech. grease

[Nyogel 774VL.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease

17.WINDOW LIFT 電動窗升降

[Rheolube 368.pdf](#)

(-40 to 125C) wide temp., elec/mech. grease

[Nyogel 774.pdf](#)

(-30 to 125C) light velvet damping feel, noise reducing

[Nyogel 774VLF.pdf](#)

(-50 to 125C) light velvet damping feel, great sub-zero operation

[UniFlor 8512.pdf](#)

(-50 to 225C) very wide temp, non oxidizing efficient grease
