

## PFOA Free, Rust Inhibited, Ultrafiltered

A PTFE thickened, heavy viscosity, perfluoropolyether grease intended for clean room applications. Benefits include good corrosion and wear prevention.

Lubricant Properties		Typical Value	Test Method
<b>Recommended Service Range (°C)</b>		-60 to 180	
<b>Thickener</b>		PTFE	
<b>Base Oil</b>	Type	Perfluoropolyether	
	Kinematic Viscosity	-40°C	2300 cSt
		40°C	140 cSt
		100°C	45 cSt
	Viscosity Index		345
	Pour Point	°C	-75
<b>Typical Properties of the Grease</b>		<b>Typical Value</b>	<b>Test Method</b>
<b>Color, Appearance</b>		White, Smooth	
<b>Penetration</b>	Unworked	285	ASTM D-217
<b>(1/10 mm)</b>	Worked	60X	301
	NLGI Grade		1.5
<b>Density</b>		25°C	1.9 g/cm <sup>3</sup>
<b>Oil Separation</b>	24 hour(s)	100°C	6.9
<b>Evaporation</b>	24 hour(s)	100°C	0.17

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product SDS for detailed safety information on this product. (1609)

Dulub Co., Ltd. [www.dulub.com.tw](http://www.dulub.com.tw) tel : 886-7-536 5500

